



[www.sealking.ca](http://www.sealking.ca)



## WOOD SEALER - DATA SHEET

### DESCRIPTION

Seal King's Wood Sealer is a translucent (semi-transparent with color) oil alkyd sealer specially formulated to penetrate deep in to the exterior wood surface, protecting the wood from rain, UV rays, snow, mildew and fungus, leaving a beautiful and lasting finish. Wood Sealer can be applied on most types of wood including pressure treated wood, pine, cedar and redwood.

### DIRECTIONS FOR APPLICATION

- Make sure surface is dry.
- If wood contains dirt build-up or paint use Seal King's Surface Preparation System to remove contaminants.
- Stir contents of pail.
- Apply with long haired natural bristle brush or roller. Applying with a sponge is highly recommended.
- If a 2nd coat is necessary then apply when sealer is touch dry, usually 2-4 hours after first application.
- Let cure for 12 hours before using.

### CAUTION

- Do not use indoors.
- This product contains flammable solvents, keep away from open flame and heat.
- Do not smoke when applying this product.
- Avoid skin and eye contact, if contact occurs wash with cold water.
- Avoid breathing vapors, use adequate ventilation.
- Keep container closed when not in use
- Store in a cool, dry place, protect from freezing.
- Keep away from children.

### BENEFITS

- Stain, sealer and preserver all in one.

- For use on decks, fences, siding log homes, shingles, spas, outdoor wooden furniture and play sets.
- Water repellent.
- Semi-transparent.
- Protection against UV sun exposure.
- Mildew and fungus resistant.
- Enhances wood grain.
- Durable and long lasting finish.

### PLEASE NOTE

- For best results apply this product in temperatures below 30°C (°F) and above 10°C (°F).
- It is recommended to do a test sample on your wood to confirm desired color and compatibility with other stain (do not use this product on top of painted surfaces)
- Maintenance of wood should take place when visually required.
- All wooden surfaces become slippery when wet. Please exercise control when walking on these surfaces.
- Use Seal King's Grease Release to clean equipment.

### COVERAGE

- 300 sq.ft/gal for smooth and 150 sq.ft/gal for rough surfaces.

### V.O.C. COMPLIANT

Product meets V.O.C. contents in accordance to E.P.A. 40 CFR pt 59 table I subpart D for Concrete Curing & Sealing Compounds with maximum V.O.C. content of **400 G/L**.

SIZES AVAILABLE:

5gal. (18.9 Ltr), 1gal. (3.79 Ltr)

FINISHES:

Cedar tone, Dark oak, Light oak, Red wood, Clear

WATER BOURNE (WB):

Available