



www.sealking.ca

BEFORE

AFTER



## WET CAST SEALER COLOR ENHANCE - DATA SHEET

### DESCRIPTION

Seal King's Wet Cast Sealer is a one component acrylic-based system. This sealer is specially formulated to enhance the natural beauty of the wet cast concrete surface by penetrating deep into the substrate, and slightly enhancing the natural colors of the concrete or pavers. This sealer will protect the concrete from oil, dirt, salt and discoloring. This sealer will not peel or blister.

### BENEFITS

- Specifically formulated for wet cast products
- Joint stabilizer
- Protects against UV rays oil, dirt & salt
- Color enhancer, low gloss
- One 5 gal pail covers approximately 500 - 1000 sq. ft.
- Rain safe after 90 minutes
- Coverage approx. 175 sq.ft. / 1 gal.

### DIRECTIONS FOR APPLICATION

- Before applying Wet Cast Sealer, the surface to be sealed must be completely clean and dry.
- Oil, grease and other contaminants should be removed before application.
- Spray, brush or roller can easily apply this product.
- Two coats are recommended for most applications
- If concrete or brick has been sealed before, we recommend testing a small area to determine compatibility.
- This sealer is touch dry in 30 minutes and can be driven on in two hours.

### CAUTION

- This product contains flammable solvents, keep away from open flames and heat, do not smoke when applying this product.
- Avoid breathing vapors, use adequate ventilation
- Keep container closed when not in use.
- Store in a cool dry place. Protect from freezing.
- Do not use indoors.

### CLEAN UP

- Clean tools with Seal King's Grease Release.

### COVERAGE

- Approximately 175 sq.ft./1gal.

### V.O.C. COMPLIANT

Product meets V.O.C. contents in accordance to E.P.A. 40 CFR pt 59 table I subpart D for Concrete Curing & Sealing Compounds with maximum V.O.C. content of **400 G/L**.

SIZES AVAILABLE:  
FINISHES:

5 gal. (18.9 Ltr), 1 gal. (3.8 Ltr)  
Color Enhance

WATER BOURNE (WB):  
WB FINISHES:

Available  
Natural Look