



www.sealking.ca



HIGH SOLIDS PARQUET ADHESIVE- DATA SHEET

DESCRIPTION

Seal King's contractors parquet adhesive is a highly durable, low odour adhesive intended for installing parquet flooring.

SURFACE PREPARATION

Floor surface must be dry, clean, free of dust, oil, grease or any foreign matter. It must also be, or made, porous (if in doubt, soak the surface with a small amount of water). If painted or varnished, it must be sanded completely. If the surface is likely to retain moisture (especially a concrete floor below grade, or in rooms with a high humidity level) a sub-floor should be built over a vapor barrier.

DIRECTIONS FOR APPLICATION

Keep the adhesive, the floor covering and the floor surface at room temperature, between 20°C (68°F) and 25°C (77°F) before, during and after application. Surfaces must be even. If surface is uneven, holes can be patched with parquet adhesive before application. Use a 5 mm (2/16") notched trowel and do not apply more adhesive than can be covered in 30 minutes. Leave approximately a 1 cm (3/8") space along the walls and permanent structures to allow for parquet to expand. Let the adhesive dry for 24 hours before washing the installation, sanding, or allowing any heavy foot traffic and replacing any furniture.

BENEFITS

- High durability.
- Fast drying.
- Low odour.
- Safe and easy to apply.
- Low VOC.

CAUTION

- Avoid skin and eye contact, if contact occurs wash thoroughly with cold water.
- Avoid breathing vapors, use adequate ventilation.
- Store in a cool, dry place, and protect from freezing.
- Keep away from children.

PLEASE NOTE

- **Do not store in temperatures below 4°C.**
- **Wear proper skin and eye protection at all times.**

V.O.C. COMPLIANT

SIZES AVAILABLE: 5gal. (18.9 Ltr)