



www.sealking.ca

BEFORE

AFTER



ASPHALT SEALER - DATA SHEET

DESCRIPTION

Seal King's Asphalt Sealer is an asphalt-water blend which cures to a hard water and weather resistant protective coating over most surfaces. Asphalt Sealer improves the appearance of older paved areas and retards the natural aging process of older paved areas and retards the natural aging process of asphaltic concrete.

USES

Recommended for sealing asphalt driveways, parking lots, tennis courts and other asphalt surfaces. Also can be used as a protective coating for some metal and wood surfaces.

PHYSICAL PROPERTIES

Color: Black
Specific gravity: 0.92 (approx).
Coverage: 2sq.m/litre
(100sq.ft./gallon-approx 500 sq.ft./gallon)
Application Temperature: 15-27°C

PREPARATION

Surface must be dry and free from all dirt, oil, grease and foreign matter. No priming is required. Minor oil spots or greasy areas must be treated with Seal King Oil Spot Primer prior to application of Asphalt Sealer. Badly oil damaged areas must be removed and patched with Seal King Cold Patch. Allow newly laid pavements and asphalt patches to cure for 90 days in warm weather before applying asphalt seal. Do not apply if rain is expected. Do not apply over coal tar surfaces.

DIRECTIONS FOR APPLICATIONS

Apply by spray, brush, or squeegee. Avoid pooling. **DO NOT DILUTE.** Addition of gasoline or other thinners will alter the product and cause the cured film to discolour (turn brown). Use caution not to over-apply if applying by brush or squeegee, curing times are longer when application rates are high. Do not apply if temperature is less than 15°C. Under favorable conditions (temperatures below 15°C, damp, cloudy weather) curing time will be extended and may take 7 days or more depending on the severity of the conditions. For best results, do not apply to hot pavement or when temperatures exceed 27°C. Do not open sealed surface to traffic until sealer has fully cured.

CLEAN UP

Use Seal King's Grease Release

SHELF LIFE

Up to 12 months in sealed containers

CAUTION

- Contains flammable solvents. Take suitable precautions.
- Use in well ventilated areas
- Keep out of reach of children

V.O.C. COMPLIANT

Product meets V.O.C. contents in accordance to E.P.A. 40 CFR pt 59 table I subpart D for Concrete Curing & Sealing Compounds with maximum V.O.C. content of **400 G/L.**

SIZES AVAILABLE:

5gal. (18.9 Ltr)