



www.sealking.ca

BEFORE

AFTER



GREASE RELEASE - DATA SHEET

DESCRIPTION

SEAL KING's Grease Release is a solvent based cleaner. It is specially formulated to remove oil, tar, coal tar, latex print, adhesives, rubber and acrylic driveway sealers from concrete surfaces.

BENEFITS

- For paving stones and concrete.
- Removes oil, tar, grease, adhesives, latex paint and driveway sealer.
- Water-soluble.
- After use simply rinse away.

DIRECTIONS FOR APPLICATION

- Apply only to concrete and paving stone surfaces.
- Let stand for 15 minutes to allow solvent to penetrate.
- Rinse the solvent with fresh water, ideally from a garden hose.
- Repeat process or use brush for more difficult stains.

CAUTION

- Keep away from open flame or spark.
- If swallowed call a first aid or poison control center immediately.
- Keep away from skin and eyes. If contact, flush with water for at least 15 minutes. For skin contact wash immediately with soap and copious amounts of water.
- Do not breathe vapor, use under well ventilated areas.
- If ingested do not induce vomiting.

PLEASE NOTE

- Do not use on asphalt surfaces.
- Use under well ventilated conditions.
- Keep container closed.
- Store in a cool dry ventilated area.
- Use lots of water when rinsing.

SIZES AVAILABLE:

1L (32oz.)