



www.sealking.ca

BEFORE

AFTER



## PAVING STONE SEALER - DATA SHEET

### DESCRIPTION

Seal King's Paving Stone Sealer is a one component acrylic-based system. This sealer is specially formulated to enhance the natural beauty of the stone, brick or concrete surface by penetrating deep into the substrate, leaving a glossy, wet looking appearance. This sealer will protect the brick or concrete from oil, dirt, salt and discoloring.

This sealer will not peel or blister.

There are three types available:

- 1) High Gloss 25% solids
- 2) Semi Gloss 12% solids
- 3) Natural Look 5 to 10% solids (silane/siloxane)

### DIRECTIONS FOR APPLICATION

- Before applying Paving Stone Sealer, the surface to be sealed must be completely clean and dry.
- Oil, grease and other contaminants should be removed before application.
- Spray, brush or roller can easily apply this product.
- Two coats are recommended for most applications
- If concrete or brick has been sealed before, we recommend testing a small area to determine compatibility.
- This sealer is touch dry in 30 minutes and can be driven on in two hours.

### CAUTION

- This product contains flammable solvents, keep away from open flames and heat, do not smoke when applying this product.
- Avoid breathing vapors, use adequate ventilation

- Keep container closed when not in use.
- Store in a cool dry place. Protect from freezing.
- Do not use indoors.

### CLEAN UP

- Clean tools with Seal King's Grease Release.

### COVERAGE

- Approximately 160 sq. ft./1 gal.

### V.O.C. COMPLIANT

Product meets V.O.C. contents in accordance to E.P.A. 40 CFR pt 59 table I subpart D for Concrete Curing & Sealing Compounds with maximum V.O.C. content of **400 G/L**.

SIZES AVAILABLE:

FINISHES:

WATER BOURNE (WB):

WB FINISHES:

5 gal. (18.9 Ltr), 1 gal. (3.8 Ltr)

Natural look, Semi-gloss,  
High-gloss

Available

Natural look, Semi-gloss,  
High-gloss