



www.sealking.ca

BEFORE

AFTER



NATURAL STONE SEALER - DATA SHEET

DESCRIPTION

Seal King's Natural Stone Sealer is a clear premium penetrating sealer specially formulated to protect, and enhance the color of flagstone and natural stone surfaces. This sealer will protect against mildew, fungus, UV rays, oils, acid rain. It will also reduce chipping, cracking due to freeze/thaw cycles.

BENEFITS

- Protects against stains, dust, acid rain, mildew, fungus, UV rays, salt, oils and efflorescence.
- Protects against the freeze/thaw cycles.
- Enhances color of stone.
- Reduces chipping, crumbling and cracking.
- Allows moisture vapor transmission.

DIRECTIONS FOR APPLICATION

- Remove any stains, dirt and other contaminants with Seal King's cleaner.
- Make sure the area to be sealed is completely dry and clean (usually 24 hours without dampness).
- Apply evenly using a brush, paint roller or pump sprayer.
- Do not allow any puddling, either mat excess sealer with deck sponge or remove with dry cloth.
- Allow 24 hours of curing time.
- For maximum protection apply a second coat.

CAUTION

- Do not use indoors.
- This product contains flammable solvents, keep away from open and heat.

- Do not smoke when applying this product.
- Avoid skin and eye contact, if contact occurs wash thoroughly with cold water.
- Avoid breathing vapors, use adequate ventilation.
- Keep container closed when not in use.
- Store in a cool dry place.
- Protect from freezing.
- Keep away from children.

PLEASE NOTE

- Always test in a small inconspicuous area before sealing total area.
- Apply in temperatures above 0°C (32°F).
- Do not seal for at least 10 days following installation of natural stone.
- Do not use over polished marble or granite or any other polished natural stone surface.
- Do not use over vitreous or semi-vitreous quarry tiles or pavers.

COVERAGE

- Covers approximately 300-2000 sq. ft./1 gal.

V.O.C. COMPLIANT

Product meets V.O.C. contents in accordance to E.P.A. 40 CFR pt 59 table I subpart D for Concrete Curing & Sealing Compounds with maximum V.O.C. content of **350 G/L**.

SIZES AVAILABLE:

FINISHES:
Oil Based

1 gal. (3.8 Ltr) 1 litre

Colour Enhancer, Natural Look