



SEAL KING

🌐 www.sealking.ca
✉ info@sealking.ca
☎ 833-933-7325

Epoxy Floor Coating- Technical Data Sheet



Description

Seal King's Epoxy Floor Coating is a non-slip attractive, 100% solids, low-odor, two-component epoxy floor coating. The non-slip additive is supplied in the kit; just mix and apply using a short nap roller. Specifically formulated for ease of use, Seal King's Epoxy Floor Coating is fast and easy to install, and can be combined with our epoxy flakes to create a customized, long lasting, durable finish.

Application Instructions

- For optimal performance, both the coating and substrate should be maintained at 18° to 30° C (68 to 86°F) for 24 hours prior to beginning work . The same temperature range should be maintained during mixing, application, and cure
- Remove oil, grease, dirt and any unsound concrete.
- Pour all liquid of component "B" into component "A" container and mix thoroughly for one minute.
- Apply the primer evenly very thin using a flat squeegee and backroll with a 6mm roller.
- Allow the primer to stand overnight before applying the topcoat (refer to the product data sheet for further information)

Available Sizes

3.78L / 1 Gallons

Available Finishes

Clear
Oyster Grey
Seal Grey

Coverage

125-150 sq. ft./Gallon

Caution

-
- Keep container closed
 - Keep away from children
 - Use only with adequate ventilation
 - Wash thoroughly after handling
 - Avoid breathing vapors
 - Avoid contact with eyes, skin and clothing
 - Do not dispose down the drains

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.