



SEAL KING

www.sealking.ca
info@sealking.ca
833-933-7325

Epoxy Primer - Technical Data Sheet



Description

Seal King's Epoxy Primer is a 100% solids, solvent-free versatile highly advanced two-component, slow curing epoxy concrete primer for indoor and outdoor concrete surfaces. It has excellent cure properties, even at low temperatures, and provides excellent adhesion to marginally prepared or otherwise hard to adhere to concrete slabs. Recommended for residential garages, balcony decks, porches, swimming pool decks and basements.

Application Instructions

- Prepare Surface, the floor must be at least 30 days old, cured, dry, clean, and free of oil.
- Combine the products (Pour the liquid from part B into part A).
- Mix the coating thoroughly using a slow speed drill with a mixing blade for approximately 1 minute until the color is uniform.
- Immediately pour some of the mixed material onto the edges of the prepared floor and spread the material evenly with a flat squeegee.
- Roll another coat once the first one is dry for best results.
- Let it cure for 24 hours before use.

Available Sizes

3.79L / 1 Gallon

Available Finishes

Primer Blue

Coverage

Primer will cover approximately 250-325 sq. ft./1 gal.

Caution

- Keep container closed Keep away from children
- Use only with adequate ventilation
- Wash thoroughly after handling
- Avoid breathing vapors
- Avoid contact with eyes, skin and clothing
- Do not dispose down the drains

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.