



**Seal King**

🌐 [www.sealking.ca](http://www.sealking.ca)

✉ [info@sealking.ca](mailto:info@sealking.ca)

☎ 833-933-7325

## Asphalt Sealer - Technical Data Sheet



### Description

---

Seal King's Asphalt Sealer is an asphalt-water blend which cures to a hard water and weather resistant protective coating over most surfaces. Asphalt Sealer improves the appearance of older paved areas and retards the natural aging process of older paved areas and retards the natural aging process of asphaltic concrete. VOC Compliant.

### Application Instructions

---

**BEFORE USE.** Surface must be dry and free from all dirt, oil, grease and foreign matter. No priming is required. Minor oil spots or greasy areas must be treated with Seal King Oil Spot Primer prior to application of Asphalt Sealer. Badly oil damaged areas must be removed and patched with Seal King Cold Patch. Allow newly laid pavements and asphalt patches to cure for 90 days in warm weather before applying asphalt seal. Do not apply if rain is expected. Do not apply over coal tar surfaces.

Apply by spray, brush, or squeegee. Avoid pooling. **DO NOT DILUTE.** Addition of gasoline or other thinners will alter the product and cause the cured film to discolour (turn brown). Use caution not to over-apply if applying by brush or squeegee, curing times are longer when application rates are high. Do not apply if temperature is less than 15°C. Under favorable conditions (temperatures below 15°C, damp, cloudy weather) curing time will be extended and may take 7 days or more depending on the severity of the conditions. For best results, do not apply to hot pavement or when temperatures exceed 27°C. Do not open the sealed surface to traffic until the sealer has fully cured

## Available Sizes

---

18.9L / 5 Gallons

## Coverage

---

Sealant will cover approximately 125 sq.ft./1 gal.

## Caution

---

- Contains flammable solvents.
- Take suitable precautions.
- Use in well ventilated areas
- Keep out of reach of children

## Warranty

---

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.