

 www.sealking.ca

 info@sealking.ca

 833-933-7325

Cold Temp Accelerator - Technical Data Sheet



Description

Seal King's COLD TEMPERATURE ACCELERATOR is specially designed to speed up set times for concrete and mortar during cold weather.

Application Instructions

- Make sure the concrete or mortar mix is free of snow and ice.
- Add ACCELERATOR to mixing water.

MIXING RATIOS

TEMP: 20°C to 10°C, 10°C to 0°C, 0°C to 5°C, -5°C to -10°C 40KG PORT CEMENT: 0.6L, 1.1L, 1.7L, 2.3L 30 KG CEMENT: 0.3L, 0.6L, 0.9L, 1.2L

Available Sizes

۱L

4L

20L

Caution

- • Avoid contact with skin and eyes. May cause Necrosis.
- Always wear safety glasses and gloves when using this product.
- See MSDS for this product.

PLEASE NOTE

- COLD TEMPERATURE ACCELERATOR does greatly reduce set up times but does not prevent the concrete or mortar from freezing.
- When using a ready mix truck, mix for at least 4-5 minutes.

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.