



SEAL KING

🌐 www.sealking.ca
✉ info@sealking.ca
☎ 833-933-7325

Concrete Sealer - Technical Data Sheet



Description

SEAL KING's Concrete Sealer is specially formulated from acrylic polymers and fast drying solvents to seal concrete, stamped or otherwise. It helps protect against oil, dirt, salt, cracking and dusting. This product has excellent water retention and color retention properties and will not inhibit the effectiveness of most floor covering adhesives for tile and carpet.

*Solids Content = 25%

Application Instructions

- Surface must be clean and free of standing water.
- Remove any oil, dirt or other contaminants.
- If the surface was previously sealed, test for compatibility by applying the product to a small surface area.
- Apply with a hand held pump sprayer or roller.
- Allow 2.5 hours for touch dry, 24 hours for full cure

Available Sizes

18.9L / 5 Gallons
3.78L / 1 Gallon

Available Finishes

High Gloss
Semi Gloss
Matte Finish

Coverage

Sealant will cover approximately 160 sq. ft./1gal.

Caution

- Do not use indoors.
- This product contains flammable solvents, keep away from open flames and heat. Do not smoke when applying this product.
- Avoid skin and eye contact, if contact occurs wash thoroughly with cold water.
- Avoid breathing vapors. Use adequate ventilation.
- Keep the container closed when not in use.
- Store in a cool dry place. Protect from freezing.
- Keep away from children.

PLEASE NOTE

- Apply only when the concrete surface is above 4°C(40°F).
- Keep vapors away from foodstuff.
- If using indoors make sure the area is well ventilated and free from open flames and sparks.
- Will not resist other solvents and gasoline.
- Use Seal King's Grease Release to clean equipment.
- V.O.C Compliant

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.