



## Paving Stone Sealer WB - Technical Data Sheet



### Description

---

Seal King's High Performance Sealer is a one component water based sealer acrylic urethane system. It is specially formulated to penetrate deep into the concrete and protect the surface from all types of weathering and harsh chemicals. This low odor sealer contains 20% solids and is available in low and high gloss. **VOC Compliant.**

### Application Instructions

---

**BEFORE YOU BEGIN** - Always test on a small hidden area to ensure that the result meets your expectation.

- Remove any oil, dirt and other contaminants with Seal King's cleaners.
- Make sure the area to be sealed is dry and clean.
- Apply with roller, brush or spray pump.
- Allow 1 hour for walking and 24 hours for parking.

### Available Sizes

---

18.9L / 5 Gallons  
3.8L / 1 Gallon

### Available Finishes

---

High Gloss  
Semi Gloss  
Natural Look

## Coverage

---

Sealant will cover approximately 100 - 200 sq. ft./l gal.

## Caution

---

- Protect from freezing.
- Avoid inhalation.
- Keep away from children.
- Avoid Skin and eye contact. If contact occurs, wash with cold water.

## Warranty

---

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.