



SEAL KING

🌐 www.sealking.ca
✉ info@sealking.ca
☎ 833-933-7325

Spall Shield Water Repellent - Technical Data Sheet (Oil Based)



Description

Seal King's Water Repellent Sealer is a siloxane solution specially formulated to protect against harsh environmental conditions. This sealer penetrates deep into the substrate leaving an invisible natural look. This product can protect your house brick, paving stone, concrete or stucco for up to 10 years.

Application Instructions

- Remove any efflorescence (whitish salt) and other contaminants with Seal King's cleaners
- Make sure the area to be sealed is completely dry and clean (Usually 24 hours without-dampness).
- Protect any areas such as windows, doors, and wood from spillage and/or splashing
- Apply with a brush, roller or spark resistant sprayer
- Use liberal amounts of sealer until the surface is completely soaked.
- One coat application is satisfactory

Available Sizes

18.9L / 5 Gallons
3.78L / 1 Gallon

Available Finishes

Natural Look

Coverage

Sealant will cover approximately 200 sq. ft./1 gal.

Caution

- This product contains flammable solvents. Keep away from open flames & heat, do not smoke when applying this product
- Avoid breathing vapours, use adequate ventilation
- Avoid skin and eye contact. If contact occurs, wash thoroughly with cold water
- Keep container closed when not in use
- Store in a cool dry place. Protect from freezing
- Do not use indoors

PLEASE NOTE

- Do not apply in temperatures below 7°C (45°F)
- Coverage may vary due to porosity of surface

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.