



SEAL KING

www.sealking.ca  
info@sealking.ca  
833-933-7325

## Wood Floor Adhesive - Technical Data Sheet



### Description

---

Seal King's contractors Wood Floor Adhesive is a highly durable, VOC compliant, low odour adhesive intended for installing wood flooring.

### Application Instructions

---

**BEFORE YOU BEGIN** - Floor surface must be dry, clean, free of dust, oil, grease or any foreign matter. It must also be, or made, porous (if in doubt, soak the surface with a small amount of water). If painted or varnished, it must be sanded completely. If the surface is likely to retain moisture (especially a concrete floor below grade, or in rooms with a high humidity level) a subfloor should be built over a vapor barrier.

Keep the adhesive, the floor covering and the floor surface at room temperature, between 20°C (68°F) and 25°C (77°F) before, during and after application. Surfaces must be even. If the surface is uneven, holes can be patched with parquet adhesive before application. Use a 5 mm (2/16") notched trowel and do not apply more adhesive than can be covered in 30 minutes. Leave approximately a 1 cm (3/8") space along the walls and permanent structures to allow for the parquet to expand. Let the adhesive dry for 24 hours before washing the installation, sanding, or allowing any heavy foot traffic and replacing any furniture.

### Available Sizes

---

18.9L / 5 Gallons

3.78L / 1 Gallons

## Benefits

---

High Durability.

Fast Drying.

Low Odour.

Safe and easy to apply.

Low VOC.

## Coverage

---

Sealant will cover approximately 50 sq. ft./1 gal.

## Caution

---

- Avoid skin and eye contact, if contact occurs wash thoroughly with cold water.
- Avoid breathing vapors, use adequate ventilation.
- Store in a cool, dry place, and protect from freezing.
- Keep away from children.

## PLEASE NOTE:

- **Do not store in temperatures below 4°C.**
- **Wear proper skin and eye protection at all times.**

## Warranty

---

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.

**7134 Wellington Road County Road #124 South, Guelph, ON N1H 6N3 Seal King is a  
Division of Korzite Coatings Inc.  
Made In Canada**