



SEAL KING

🌐 www.sealking.ca
✉ info@sealking.ca
☎ 833-933-7325

Wood Stain Sealer - Technical Data Sheet



Description

Wood stain sealer is a water-based oil designed for the protection of outdoor wooden decks, poolside decks and garden furniture. It does not flake, and has excellent resistance to water and sun. Ready to use, easy to use. For use of maintenance or renewal, it does not require sanding

Application Instructions

- Application: Brush or roller.
- Stir before use.
- Do not paint at temperatures below 10 ° C / 50 ° F.
- Tool cleaning: wash with water immediately after use.

Available Sizes

18.9L / 5 Gallons

3.78L / 1 Gallon

250ml / 8.45 oz

Coverage

Sealant will cover approximately 500 sq. ft./1gal.

Caution

- This product contains flammable solvents. Keep away from open flames & heat, do not smoke when applying this product
- Avoid breathing vapours, use adequate ventilation
- Avoid skin and eye contact. If contact occurs, wash thoroughly with cold water
- Keep container closed when not in use
- Store in a cool dry place. Protect from freezing
- Do not use indoors

PLEASE NOTE

- Always shake the products well before use.
- After use, it is advisable to always close the package carefully. In case of decanting, use only containers made of suitable material, such as polyethylene and stainless steel.
- For best aesthetic results, prepare the substrate paying attention to sanding. Colorless paint systems do not offer optimal resistance.
- At the end of processing, wash the tools used thoroughly with water. The final result of the painting cycle is the sole responsibility of the user, who must make sure that the product corresponds to their needs.

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.