



SEAL KING

🌐 www.sealking.ca
✉ info@sealking.ca
☎ 833-933-7325

Epoxy Crack Filler - Technical Data Sheet



Description

Seal King's Epoxy Crack filler is a 100% solid, two-component epoxy-based crack filler, which has a butter-like texture, designed to repair and fill both vertical or horizontal cracks and small holes.

Application Instructions

- New concrete must be cured for a minimum of 28 days before applying.
- The substrate must be above 10C (50F) and must be free of all dirt, waxes, previously applied coatings, oil, grease, laitance and any foreign matter that may interfere with the bond of the prepared substrate.
- All concrete surfaces to be treated should be shot blast, or mechanically cleaned for the best results.
- Premix each component separately before using. Combine 1 part (by volume) of Part A with 1 part (by volume) of Part B.
- Mix with a low speed drill.
- Thoroughly blend the material until an even consistency is achieved, periodically scrape down the sides and the bottom of the container. Apply as soon as possible as the pot life is limited.

Available Sizes

Available Finishes

0.5L / 0.13 Gallons

Clear

Grey

Coverage

1.0m/0.5L

Caution

-
- Store in a well ventilated area, keep the container tightly shut.
 - Product is not recommended for applications where ambient temperatures are below 10C (50F) or for underwater repair.
 - Store in a heated warehouse. Storage at temperatures below 4.5C (40F) may cause the resin to crystallize.

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.