



SEAL KING

🌐 www.sealking.ca
✉ info@sealking.ca
☎ 833-933-7325

Grease Release - Technical Data Sheet



Description

SEAL KING's Grease Release is a solvent based cleaner. It is specially formulated to remove oil, tar, coal tar, latex print, adhesives, rubber and acrylic driveway sealers from concrete surfaces

Application Instructions

- Apply only to concrete and paving stone surfaces.
- Let stand for 15 minutes to allow solvent to penetrate.
- Rinse the solvent with fresh water, ideally from a garden hose.
- Repeat the process or use a brush for more difficult stains.

Available Sizes

1L / 32oz

Caution

- Keep away from open flame or spark.
- If swallowed call a first aid or poison control center immediately.
- Keep away from skin and eyes. If contact, flush with water for at least 15 minutes. For skin contact wash immediately with soap and copious amounts of water.
- Do not breathe vapor, use under well ventilated areas.
- If ingested do not induce vomiting

PLEASE NOTE

- Do not use it on asphalt surfaces. Use under well ventilated conditions.
- Keep the container closed.
- Store in a cool dry ventilated area.
- Use lots of water when rinsing

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.