



SEAL KING

🌐 www.sealking.ca
✉ info@sealking.ca
☎ 833-933-7325

Lacquer Thinner - Technical Data Sheet

Description

This product can be used to strip sealer from paving stone and concrete.

Application Instructions

- Make sure the area is completely dry and free of water.
- Apply LACQUER THINNER on the surface.
- Scrub with nylon scrub brush for 1 minute. DO NOT use a steel brush.
- Soak up loose sealers with a dry, clean rag or use a high output pressure washer.
- Repeat process if necessary

Available Sizes

Available Finishes

18.9L / 5 Gallons

N/A

3.78L / 1 Gallon

Caution

- Do not use indoors.
- This product contains flammable solvents, keep away from flames and heat. Do not smoke when applying this product.
- Avoid skin and eye contact, if contact occurs wash thoroughly with cold water.
- Avoid breathing vapors. Use adequate ventilation.
- Keep the container closed when not in use.
- Store in a cool dry place. Protect from freezing.
- Keep away from children.

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.