



Seal King

www.sealking.ca
info@sealking.ca
833-933-7325

Masonry - Technical Data Sheet



Description

Seal King's Masonry Sealer is a siloxane solution specially formulated to protect against harsh environmental conditions. This sealer penetrates deep into the substrate leaving an invisible natural look. This product can protect your house brick, paving stone, concrete or stucco for up to 10 years.

Application Instructions

- Remove any efflorescence (whitish salt) and other contaminants with Seal King's cleaners
- Make sure the area to be sealed is completely dry and clean (Usually 24 hours without dampness).
- Protect any areas such as windows, doors, and wood from spillage and/or splashing
- Apply with a brush, roller or spark resistant sprayer
- Use liberal amounts of sealer until surface is completely soaked.
- One coat application is satisfactory

Available Sizes

18.9L / 5 Gallons
3.78L / 1 Gallons

Available Finishes

Natural Look

Benefits

- Quick drying on all neutral and alkaline substrates. This means that the beading effect is noticeable within a few hours of application
- Very slight change in the material's natural porosity
- Outstanding resistance to aging agents such as U.V., freeze thaw cycles, acid rain and calcium
- Non toxic
- Excellent stability during storage

Coverage

Sealant will cover approximately 125 sq.ft./1 gal.

Caution

- This product contains flammable solvents, keep away from open flames and heat, do not smoke when applying this product
- Avoid breathing vapours, use adequate ventilation
- Avoid skin and eye contact. If contact occurs, wash thoroughly with cold water
- Keep container closed when not in use
- Store in a cool dry place. Protect from freezing
- Do not use indoors

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.