

Paving Stone Sealer - Technical Data Sheet



Description

Seal King's Paving Stone Sealer is a one component solvent-based, VOC compliant, acrylic based system. This sealer is specially formulated to enhance the natural beauty of the stone, brick or concrete surface by penetrating deep into the substrate, leaving a glossy, wet looking appearance. This sealer will protect the brick or concrete from oil, dirt, salt and discoloring. This sealer will not peel or blister.

Application Instructions

BEFORE YOU BEGIN - Always test on a small hidden area to ensure that the result meets your expectation.

- Before applying Sealer, the surface to be sealed must be completely clean and dry.
- Oil, grease and other contaminants should be removed before application.
- Spray, brush or roller can easily apply this product.
- Two coats are recommended for most applications
- This sealer is touch dry in 30 minutes and can be driven on in 8 hours.

Available Sizes	Available Finishes
18.9L / 5 Gallons	High Gloss
9.45L / 2.5 Gallons	Semi Gloss
3.78L / I Gallons	Matte Finish
	Natural Look

Coverage

Sealant will cover approximately 100 - 200 sq. ft./Igal.

Caution

- This product contains flammable solvents, keep away from open flames and heat, do not smoke when applying this product.
- Avoid breathing vapors, use adequate ventilation
- Keep the container closed when not in use.
- Store in a cool dry place. Protect from freezing.
- Do not use indoors.

Warranty

Our ISO 9001 audit procedures confirm strict quality control of our products in manufacture within approved tolerances. Our products are warranted to be free of defects in material or manufacture. If a product does not conform to this warranty, Seal King's sole obligation under this warranty shall be, at its option, to credit the Purchaser's account or to supply replacement material. All information and recommendations given in this document are accurate on the date of publication.

Please consult the Safety Data Sheet for more Hazard Information.